

## ELIO

**Incasso architettonico  
con proiettore estraibile.**



*Architectural recessed  
luminaire with extractable  
projector.*

Proiettori professionali per incasso in controsoffitto in cartongesso. Realizzati in pressofusione di alluminio. Versione per installazione con anello di battuta. Orientabilità rispetto la verticale 90° e rotazione di 360°. Ottica secondaria antiabbagliamento per un elevato confort visivo. Disponibile in finitura bianca con coilex controllo abbagliamento nero. Fornito completo di driver ON-OFF. Dimmerabile DALI su richiesta. Grado di protezione IP20, classe di isolamento III, marchio F.



*Professional projectors for recessed installation in plasterboard false ceilings. Made of die-cast aluminium. Version for installation with stop ring. 90° vertical adjustability and 360° rotation. Secondary anti-glare optics for high visual comfort. Available in white finish with black glare control coilex. Supplied complete with ON-OFF driver. DALI dimmable on request. Protection degree IP20, insulation class III, F mark*





Item: RAER081--  
Power: 8W  
Beam angle: 32°  
Output flux: 670 lm  
Temp. Color: 3.000K  
CRI: >90  
Face ring: black  
Driver: on-off (F), Dali (D)  
IP20



Item: RAES081--  
Power: 8W  
Beam angle: 32°  
Output flux: 670 lm  
Temp. Color: 3.000K  
CRI: >90  
Face ring: black  
Driver: on-off (F), Dali (D)  
IP20



Item: RAES082--  
Power: 2x8W  
Beam angle: 32°  
Output flux: 670 lm  
Temp. Color: 3.000K  
CRI: >90  
Face ring: black  
Driver: on-off (F), Dali (D)  
IP20



### CODIFICA PRODOTTI / PRODUCT CODING

Family name	With ring Round\Square	Power LED (W)	Numer Projectors	Type of driver On-off\Dali	Temp.color K
RAE	R \ S	08	1 \ 2	F \ D	3000K