

AURA

Faretto incasso orientabile
compatto

*Compact adjustable recessed
spotlight.*

Proiettori professionali orientabili per incasso in controsoffitto in cartongesso. Realizzati in pressofusione di alluminio. Questo faretto si contraddistingue per il diametro del foro particolarmente ridotto. Disponibile con anello di battuta in colore bianco o nella versione trimless a rasamento. Equipaggiato con lente Fresnel e Ottica secondaria antiabbagliamento per un elevato confort visivo (UGR<15), disponibile in finitura nero cromo e bianca. Grado di protezione IP20, vano ottico IP44, classe di isolamento III, marchio F. Fornito completo di driver ON-OFF. Dimmerabile DALI su richiesta.






Professional adjustable projectors for recessed installation in plasterboard false ceilings. Made of die-cast aluminum. This spotlight is characterized by the particularly small hole diameter. Available with white stop ring or in the trimless version. Equipped with Fresnel lens and anti-glare secondary optic for high visual comfort (UGR <15), available in black chrome and white finish. Degree of protection: IP20, optics IP44, electrical insulation class III, F mark. Supplied complete with ON-OFF driver. DALI dimmable on request.



Item: RFA418T - -
Power: 8W
Beam angle: 38°
Output flux: 565 lm
Temp. Color: 3.000K
CRI: >90
Face ring: trimless
Driver: on-off (F), Dali (D)
IP20, O IP44



Item: RFA508R - -
Power: 8W
Beam angle: 38°
Output flux: 565 lm
Temp. Color: 3.000K
CRI: >90
Face ring: white
Driver: on-off (F), Dali (D)
IP20, O IP44



CODIFICA PRODOTTI / PRODUCT CODING

Family name	Dimension hole	Power LED (W)	With ring/trimless	Type of driver On-off/Dali	Optical finish Black chrome/white
RFA	41 \ 50	8	T \ R	F \ D	1 \ 2